

Brilliant Wonders.®

LED BUBBLERS

LED BUBBLER FOR GUNITE, VINYL & FIBERGLASS POOLS

Bright, Efficient Fountain Feature

Smart Sync® Technology

Stream Shoots over 30 Inches High

Seamless, Flush Installation



CMP POOL
PRODUCTS

c-m-p.com/brilliant-wonders-led-bubbler

The Next Pool You Build Should Be Brilliant™

Brilliant Wonders® LED Bubblers shoot dramatic streams of water into the air in vivid display of LED color. A perfect feature for sun shelves, tanning ledges, beach entries, ponds, fountains and more. This is the ONLY LED Pool Bubbler that can be installed in gunite, vinyl & fiberglass pools.



PRODUCT FEATURES

- Bright & Efficient Cree® LEDs
- Uses Only 20 Watts for High Output LED Performance
- Built-in Smart Sync® Technology
- Exciting Streams of Water up to Over 30 Inches High
- Non-Metallic Design: No Bonding, No Grounding
- Flush Finish Installation
- Completely Serviceable from the Top
- LED Light is Below the Water Surface 4-12 inches
- ETL Listed



Gunite Unit



Gunite Unit with optional vinyl/fiberglass kit



BUILT-IN CMP SMART SYNC® TECHNOLOGY

Available with Smart Sync programming to synchronize with all other Brilliant Wonders LED Lighting products, and lighting or controls from major pool OEMs. No other external control system is required for synchronization.



VINYL & FIBERGLASS INSTALLATION OPTIONS

Choose a Gunite Bubbler from above and Vinyl/Fiberglass Kit. Every complete kit includes everything needed to install in a vinyl or fiberglass in ground pool.



EXCLUSIVE FOUNTAIN EFFECT ACCESSORIES

Combine with Brilliant Wonder LED Fountain Accessories to create the only built in LED fountain for in ground pools. Brilliant Wonders® Fountain Accessories come fully assembled and ready to install.

TECHNICAL GUIDE

- 1" conduit
- 1½" or 2" PVC pipe (1.5" S x 2" SP)
- ¾" or 1/2" adjustable eyeball
- 10-40 Gallons per minute
- 4" to 12" water depth / Max depth 36"
- 25, 50, 100 or 150 foot cord
- 12 Volt AC, 1.6 AMP, 20 Watts
- Requires 12V AC transformer (not included)

Plume Height At Given Water Depths

	1/2" REDUCER					3/4" REDUCER				
	4"	6"	8"	10"	12"	4"	6"	8"	10"	12"
10gpm	13	7								
15gpm	30	20	13	10	8	9	6	4.5	3.5	2
20gpm	55	34	24	18	13	13.5	10	8	6.5	4.5
25gpm	-	-	38	28	20	20	15	12	9.5	7
30gpm	-	-	-	-	-	28	21	16	12.5	10
35gpm	-	-	-	-	-	38	29	20.5	16	13
40gpm	-	-	-	-	-	-	37	26	20	16

21.1mm Nozzle with 2" Piping | Water height may vary